

INQUIRY

ORDER

SLC Sautter Lift Components

GmbH & Co. KG

Borsigstraße 26

70469 Stuttgart, Germany

Phone: 0711 - 860 62 0

Fax: 0711 - 860 62 501

Email: info@slc-liftco.com

Order no.:

Customer:

Delivery address:

Cust. order no.:

Serial no.:

Comm. no.:

Processor:

Date:

Required date:

ACCESSORIES Progressive safety gear BF

Deflection lever standard A=500	506.000.167	30x30x2 straight for standard	506.000.187
Deflection lever Standard A=1000	506.000.167	30x30x2 straight for tandem/triple	506.000.510
Deflection lever order-bound	847.944	30x30x2 cranked for standard	506.000.188
Deflection lever extension	106.700.355	30x30x2 cranked for tandem/triple	506.000.511
Pull rod 3500	106.930.259	Rope clamps 6,5 mm	101.350.170
PU extension for safety gear ZFII	506.000.102	Rope clamps 8,0 mm	101.350.110
PU extension for safety gear RF II	506.000.103	PU lubricator 9/10 mm	101.120.060
PU extension for RF-1 or GK1	506.000.169	PU lubricator 16 mm	101.120.050
PU extension for safety gear F1	506.000.170	Accessory for guide shoe mounting	847.848
PU extension for safety gear T1	506.000.171	PU guide shoes FS 140/9,5	506.000.501
PU extension for safety gear T3BR	506.000.172	PU guide shoes FS 140/10,5	506.000.502
PU extension for safety gear T5BR	506.000.173	PU guide shoes FS 140/16,5	506.000.503
Neutral position	50.100.243	PU guide shoes FS 150/9	506.000.504
PU accessory for pull rod 6,5 mm	106.850.442	PU guide shoes FS 150/16	506.000.505
PU accessory for pull rod 8,0 mm	106.850.441	PU guide shoes FS 190/16	506.000.506
PU brake shoes for rotary disc	506.000.183	PU guide shoes FS 250/16	506.000.507
PU brake shoes counter brake shoe	506.000.104	PU guide shoes FS 300/16	506.000.509
PU distance plates 0,25 mm	506.000.189	Roller switch with locking	506.000.184
PU distance plates 0,5 mm	506.000.192	Roller switch without locking	506.000.185
PU mounting parts Standard	506.000.481	Roller switch EX with locking	506.000.186
PU mounting parts Tandem/Triple	506.000.482	Cable loop length = 5 m	504.014.007
Safety gear shaft 20x20x2 straight	506.000.174	Cable loop length = 8 m	504.014.008
Safety gear shaft 20x20x2 cranked	506.000.175		